Technical Data Sheet

Product Specifications



Oatlands

Product Details			
Technical Data		Technical Data	
Туре	Luxury Vinyl Plank	Colours	8
Total Thickness	2.0mm	Protective Coating	PUR Coating
Wear Layer	0.30mm	Finish	Phthalate Free
Dimensions	1227mm (L) x 187mm (W)	Surface	Woodgrain
Planks per Box	16	Profile	Square Edge
M² per Box	3.671m²	M² per Pallet	330.39 m²
Weight per Box	13.7kg	Installation Method	Glue down – Refer to Installation instructions for further details.
Performance			
Class Rating	23, 31		ISO 10582
Dimensional Stability	≤ 0.10%		EN 434
Abrasion Rating	Group T		EN 660-2
Residual Indentation	<0.05mm		EN 433
Furniture Leg	No Damage		EN 424
Castor Chair	No Damage		EN 425
Impact Sound Reduction	ΔLw =4dB IIC = 65		EN ISO 140-8 ASTM E492-09
Thermal Performance (Underfloor heating)	0.07 m2 k/W (suitable – max. 27° C)		EN 12667
Light Fastness	≤ Grade 6		EN ISO 105-B02
Chemical Resistance	Good		EN 423
Electrical Propensity	Pass		EN 1815
Slip Resistance	P3, R10		AS/NZ 4586-2013
Light Commercial Warranty	5 Years		
Residential Warranty	20 Years		
Reaction to Fire	Critical Radiant Flux 10.7 kW/m2 Smoke Value 25 %.min		AS/ISO 9239.1-2003
VOC Rating	Available on Request		
Recommended Adhesive	Polymer 265 Adhesive – General application Roberts GS200 – Universal Vinyl Adhesive, Solvent Free, Low VOC, Green Star Compliant		







