BUSHLANE



September 2019 V 1

Technical Data Sheet

LAMINATE

Product Specifications









Product Details				
Technical Data				
Туре	Laminate	Laminate		6
Total Thickness	8.0mm	8.0mm		Ultra HDF / Melamine Resin
Wear Layer	Aluminium Oxide	Aluminium Oxide		Matte
Dimensions	1215mm (L) x 194mm (1215mm (L) x 194mm (W)		Embossed
Planks per Box	10	10		Square Edge
M² per Box	2.3571 m ²	2.3571 m ²		141.426 m²
Weight per Box	16.5kg	16.5kg		Glue-free mechanical locking system
Performance				
Abrasion Resistance	AC3	AC3		EN 13329
Impact Resistance	IC2	IC2		EN 13329
Resistance to staining	Group 1,2: Class 5	Group 1,2: Class 5		EN 438
Light Fastness	> Level 6 Blue Scale	> Level 6 Blue Scale		EN ISO 105-B02
Static Indentation	< 0.01mm – No visible	Change		
Furniture Leg	No Change	No Change		EN 424
Castor Chair	No Change	No Change		EN 425
Thickness Swelling	≤ 18%	≤ 18%		EN 13329-F
Reaction to Fire	Critical Radiant Flux Smoke Value	4.5 kW/m2 19 %.min	Conforms for all BCA Buildings	AS/ISO 9239.1-2003
Slip Resistance	P2			AS/NZ 4586-2013
Formaldehyde	< 0.1%	< 0.1%		ENV717-1
Commercial Warranty	10 Years			
Residential Warranty	25 Years			
Sustainability				
VOC Rating	E1 compliant for VOC	E1 compliant for VOC emission rate limits		

All product specifications and colourations are subject to nominal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice.

All product is manufactured under a management system certified as complying with ISO9001 & ISO14001.

All Airstep Flooring products must be installed in accordance with relevant Australian Standards and in conjunction with the Airstep Flooring Installation Instructions. Airstep Flooring reserves the right to change the specifications or delete colours of this product without notice. Test results and certificates are available on request.

Warranty terms and conditions apply.

For Installation Instructions, Cleaning, Care & Maintenance Instructions, see www.airstepflooring.com.au