



imagine[®]
floors by Airstep.

Drilay
Hard Flooring Underlay

ACCESSORIES



AIRSTEP

What is Drilay?

Drilay is a 2mm thick Polyethylene Foam underlay with an in-built moisture barrier. It is designed to provide moisture protection without any of the bells or whistles.

What makes Drilay budget friendly?

Drilay is a no frills underlay. While it provides a sufficient moisture barrier to assist in preventing the transference of moisture and vapours from the subfloor to your flooring, it does not go above and beyond. Many of our other underlays offer multiple benefits, hence the price difference between Drilay and these options.

Where should Drilay be installed?

Drilay is suitable for installation beneath both Laminate and Timber floating floors. We suggest the installation of Drilay in situations where budget is the most important factor in decision making.

How is Drilay installed?

Drilay is a loose lay installation underlay.

What does the R Rating mean?

The R rating of an underlay refers to how much thermal insulation an underlay provides. The higher the R rating, the more comfort an underlay will provide in terms of temperature fluctuations in the space due to loss of heat through the floor.

Thermal properties must always be measured as a system, rather than on a product by product basis. As such, we recommend checking the R rating of your chosen flooring as well.

What is the acoustic rating?

Drilay achieves a 3 star acoustic rating when paired with 14/3mm Timber flooring. This rating is BCAA compliant. Acoustics should be measured in-situ to provide an accurate rating, as there are many factors that impact the overall score.



Product Code: 2100809

Support without breaking the bank



At just 2mm thick Drilay isn't at all intrusive, but it's still strong and thick enough to get the job done. Designed to provide a moisture barrier between your floors and subfloors, Drilay is budget friendly and offers small amounts of acoustic benefit.

Roll Length (m)	Roll Width (m)	Thickness (mm)	Density (kg/m ³)	Acoustic Performance W.S.I Noise Level [LnT] (dB)	Thermal Insulation R Rating (m ² K/W)
20	1+ 65 mm overlap	2	82	51*	0.07

*Tested with 14/3mm Timber

Laminate or Timber Floating Floor

Polyethylene Foam

Moisture Barrier



While the installation of flooring such as Hybrid or Luxury Vinyl Plank with a waterproof surface throughout your home can protect your floors from moisture damage from above, the foundation of your design is still susceptible to moisture rising up through your subfloors and causing damage. Luckily, the installation of underlayment can help combat this issue.

Our Drilay Underlay helps offer a solution to this, as it is designed to assist in reducing moisture transference in order to help protect floating floors while also providing a small level of acoustic reduction.