

Technical Data Sheet

Product Specifications

imagine™
floors by Airstep.

Naturel Plank 3.0

VINYL PLANK

Product Details

| Technical Data | | Technical Data | |
|------------------------|----------------------------|---------------------------|---|
| Type | Luxury Vinyl Plank | Colours | 12 |
| Total Thickness | 3.0mm | Protective Coating | PU Coating |
| Wear Layer | 0.50mm | Finish | Phthalate Free |
| Dimensions | 1219.2mm (L) x 177.8mm (W) | Surface | Woodgrain – Semi Wild |
| Planks per Box | 15 | Profile | Square Edge |
| M ² per Box | 3.26 m ² | M ² per Pallet | 179.30 m ² |
| Weight per Box | 16.5kg | Installation Method | Glue down – Refer to Installation instructions for further details. |

Performance

| | | | |
|--|---|------------------------------------|----------------------------------|
| Class Rating | 23, 32 | | ISO 10582 |
| Dimensional Stability | ≤ 0.25% | | EN 434 |
| Abrasion Rating | Group T | | EN 660-1 |
| Residual Indentation | ≤0.1mm | | EN 433 |
| Furniture Leg | No Damage | | EN 424 |
| Castor Chair | No Damage | | EN 425 |
| Impact Sound Reduction | Δ Lw = 6dB | | EN ISO 717-2 |
| Curl Resistance to Heat | ≤ 2mm | | EN 434 |
| Thermal Performance (Underfloor heating) | 0.07 m ² kW (suitable – max. 27° C) | | EN 12667 |
| Light Fastness | ≥ 6 | | EN ISO 105-B02 |
| Chemical Resistance | Class 0 | | EN 423 |
| Electrical Propensity | 0.5kV | | EN 1815 |
| Slip Resistance | P2, R10 | | AS/NZ 4586-2013 |
| Commercial Warranty | 10 Years | | |
| Residential Warranty | 25 Years | | |
| Reaction to Fire | Critical Radiant Flux Smoke Value Bfl-S1 | 6.1 kW/m ² 148 %.min | AS/ISO 9239.1-2003 EN 13501-1 |
| VOC Rating | Available on Request | | |
| Recommended Adhesive | Polymer 265 Adhesive – General application Roberts GS200 – Universal Vinyl Adhesive, Solvent Free, Low VOC, Green Star Compliant Holdfast 416 – Multi Purpose Sheet and Tile Adhesive | | |

• 100% Recyclable

• Bio-based Plasticisers



All specifications and colourations are subject to normal manufacturing tolerances. Materials supply and/or manufacturing process may be changed without notice. All product is manufactured under a management system certified as complying with ISO9001 & ISO14001. Airstep Flooring products must be installed in accordance with relevant Australian Standards and in conjunction with the Airstep Flooring Installation Instructions.

Airstep Flooring reserves the right to change the specifications or delete colours on this product without notice. Test results and certificates are available on request. Warranty terms and conditions apply.

For Installation Instructions, Cleaning, Care & Maintenance Instructions, see www.airstepflooring.com.au

Airstep Flooring Pty Ltd 20 South Gippsland Hwy Dandenong South, VIC 3175 | www.AirstepFlooring.com.au | ABN: 97 604 980 798